

502



502 Seals are full convolution elastomeric bellows designed for confined spaces and limited gland depths. Self aligning feature compensates for excessive shaft end play and run out.

Main Characteristics

Mostly use:

Temp. In seal chamber:

Pressure in seal chamber:

Linear velocity:

Pressure:

Speed:

Oil, water and other low corrosion mediums


-30°C to 220°C

< 4mpa

< 20 m/sec

40 bar

13 m/s



	d	D	D1	L	L1
14mm	14,0	24,0	25,0	34,75	23,3
16mm	16,0	26,0	27,0	34,75	23,3
18mm	18,0	32,0	33,0	37,3	24,3
20mm	20,0	34,0	35,0	37,3	24,3
22mm	22,0	36,0	37,0	37,3	24,3
24mm	24,0	38,0	39,0	39,8	27,0
25mm	25,0	39,0	40,0	39,8	27,3
28mm	28,0	42,0	43,0	42,3	30,3
30mm	30,0	44,0	45,0	42,4	30,8
32mm	32,0	46,0	48,0	42,4	30,8
33mm	33,0	47,0	48,0	42,4	30,8
35mm	35,0	49,0	50,0	43,4	30,8
38mm	38,0	54,0	56,0	44,9	32,3
40mm	40,0	56,0	58,0	44,9	32,3
43mm	43,0	59,0	61,0	44,9	32,3
45mm	45,0	61,0	63,0	44,9	32,3
48mm	48,0	64,0	66,0	45,5	32,3
50mm	50,0	66,0	70,0	47,4	34,3
53mm	53,0	69,0	73,0	47,4	34,3
55mm	55,0	71,0	75,0	47,4	34,3
58mm	58,0	78,0	78,0	52,4	39,3
60mm	60,0	80,0	80,0	52,4	39,3
63mm	63,0	83,0	83,0	52,4	39,3
65mm	65,0	85,0	85,0	51,6	39,3
68mm	68,0	88,0	90,0	52,6	39,3
70mm	70,0	89,0	92,0	60,2	45,3
75mm	75,0	96,0	97,0	60,2	45,3
80mm	80,0	104,0	105,0	60,2	45,3
85mm	85,0	108,0	110,0	60,2	45,3
90mm	90,0	114,0	115,0	65,2	50,3
95mm	95,0	118,0	120,0	65,2	50,3
100mm	100,0	124,0	125,0	65,2	50,3